

Serial No. 10/718,058

Amendments to the Specification:

Please replace paragraph on page 5 beginning with line 1 with the following amended paragraph:

Fig. 3 is a view like ~~Fig. 2~~ showing sling panels separated away from a pillow retained in the sling;

Please replace paragraph on page 6 beginning with line 11 with the following amended paragraph:

An insert pillow 18 is received into the sling, as for example downwardly when connection 16 is opened as seen in Fig. 5. The received pillow is located in space 20, between arm space 15 and panel 10a, whereby the pillow comfortably holds the user's arm 12b in outwardly spaced relation to the user's side 14, the tensioned sling panel 10b holding the user's arm against the pillow side 18a. The pillow may consist of yieldably compressible pad material 22 such as foam rubber, or foam plastic, and a jacket 23 surrounding the pad, as at 23a-23d, in Fig. 7. A finger or hand retention strap 24 extends adjacent the forward end of the pillow at its side facing space 15. The strap lower end 24a has ~~VELCRO~~ hook and loop connection to the pillow, bottom panel 10e as at 70.

Serial No. 10/718,058

Please replace paragraph on page 7 beginning with line 5 with the following amended paragraph:

Sling strap 11a has connection to upper portions 10a' and 10b' of both sling panels 10a and 10b, as seen in Fig. 7. See ring 30 connecting adjustable strap ~~31~~ 32 to loop ~~32~~ 32a; and see ring 33 connecting adjustable strap ~~31~~ 32b to loop 32. Ring 35 connects loop 32 to sling shoulder strap 11a, as shown. ~~VELCRO~~ Hook and loop connections 31a and 34a allow length adjustment of folded-back straps 31 and 34 whereby rotary positioning (see arrow 50) of the pillow in the sling can be achieved; and ~~VELCRO~~ hook and loop connection 37 allows length adjustment of sling strap 11b.